

SPECIFICATIONS

Headliner™ 410 Bass Cabinet



Frequency response, 1 meter on-axis, swept-sine in anechoic environment:

48 Hz to 6 kHz

Power handling:

400W RMS
800W program
1600W peak

Transducer complement:

Four 10" heavy-duty ferrite magnet woofers

Impedance (Z):

8 ohms

Input connections:

One 4-pin twist-lock connector, in parallel with two 1/4" phone jacks.

Enclosure:

Internally braced cabinet in black carpet, with a full coverage 16 ga. perforated metal grille.

Transport provisions:

Steel handles, one on each side

Dimensions (H x W x D):

24.00" x 23.38" x 18.38
610 mm x 594 mm x 467 mm

Net weight:

72 Lbs. (32.7 kg)

Features:

- 4 Custom designed ceramic magnet 10" woofers
- 800W program power handling
- 8 ohm impedance
- Internal cabinet bracing
- Durable black carpet covering
- 16 Ga. Perforated metal grille
- Two 1/4" input jacks, and one 4-pin twist-lock connector
- Steel corners for road durability

Description:

The new Headliner™ series has been re-designed from the ground up for the serious bass player on a budget. Voiced for tight punchy bass with lots of harmonic tone, the versatility and performance of the Headliner™ 410 encourages use with any fine bass amp head.

The Headliner™ 410 is constructed using internal bracing, and is covered with road-worthy black carpet. Steel corners protect the cabinet from the rigors of the road. The cabinet includes a black powdercoat finished 16 gauge perforated metal grille.

The four 10" ferrite magnet woofers are designed with a rich bass tone

in mind. The sealed cabinet insures tight bass notes, with every note rendered precisely. Inputs include two 1/4" input phone jacks, and one 4-pin twist-lock connector for maximum flexibility.

With a nominal impedance of 8 ohms, and a power handling of 800 watts program and 1600 watts peak, the Headliner™ 410 can be used in conjunction with any reasonably sized bass amp head. With the 8 ohm impedance, the Headliner™ 410 can be easily stacked with a Headliner™ 210 cabinet on top, resulting in a 4 ohm total load.

Be sure to check the amplifier specifications to verify the minimum impedance rating of the amp used to power the stacked pair of speakers.

3 + 2 YEAR LIMITED WARRANTY

NOTE: For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box 2898, Meridian, Mississippi 39301-2898, or on our website at <http://www.peavey.com/support/warrantyregistration/warrantytext.cfm>.



Logo referenced in Directive 2002/96/EC Annex IV (OJ(L)37/38, 13.02.03 and defined in EN 50419: 2005. The bar is the symbol for marking of new waste and is applied only to equipment manufactured after 13 August 2005.

Features and specifications subject to change without notice.

Peavey Electronics Corporation • 5022
Hartley Peavey Drive • Meridian, MS • 39305
(601) 483-5365 • FAX (601) 486-1278
www.peavey.com ©2010 EX000076

